


ENGAGING SELF SERVICE AT THE TOUCH OF A BUTTON

Take your unattended transactions to the next level with the UX 100 and UX 110 PIN pad. These secure modules work with other UX Solutions to meet self-service demands indoors and out. Featuring an LCD screen that helps guide the customer experience, the UX 100 offers high performance and excellent durability. And with its weatherproof construction, the UX 110 is ideal for on-street parking meters, petroleum pumps, ticketing machines and more. Pair them with the UX 300 card reader to optimize your transaction functionality. Simple to integrate, the UX Series features flexible configuration settings, with easy, single cable connection between devices.



UX 110



UX 100

DELIVERING MAXIMUM SECURITY AND DURABILITY

- Latest PCI 3.x security standard certification and meets international security requirements
- EMV level 2 certified when connected to UX 300
- Durable metal front plate and weatherproof enclosure provides top-level protection against dust, liquids and other harmful substances withstanding IP65
- Anti-vandalism enclosure can withstand an impact up to 10 Joules (IK09)

ENGINEERING SEAMLESS INTEGRATION

- Fast and painless installation – thanks to plug-and-play functionality and standard USB connection
- Bus-powered device, no extra power supply requested

DRIVING THE CONSUMER EXPERIENCE

- Engage the consumer at point of sale through messaging and upselling on the large, secure 2.5" monochrome graphic LCD display with white backlit (UX 100 only)
- High contrast and readability within low temperatures and direct sunlight (UX 100 only)
- Customize your UX Series PIN pad with customer-specific texture
- Powerful controller for maximum operation speed
- Embossed and color-marked symbols comply with disability laws

Processor

400 MHz ARM11 32-bit RISC processor

Display

128 x 64 pixels
White backlit

Keyboard

Approved for 2,000,000 cycles
10 + 6 key keypad:
– 10 numeric keys (0-9)
– 4 colored keys
– 2 navigation keys

Communication and Connectivity

USB B 2.0 full speed

Security

PCI PED 3.x certified

Environmental condition

-20°C to +70°C @ 10-90% humidity

Physical dimension (l x w x h)

142 x 108 x 26 mm (UX 100)
101 x 108 x 26 mm (UX 110)

Mechanics (cutout)

120 x 82mm (UX 100)
75 x 75mm (UX 110)

